3099979 | 050G135PP200R0PE

ConQuest® Empty Conduit, 1/2 in, SDR 13.5, gray, with pull rope



Product Classification

Product TypeEmpty conduitProduct BrandConQuest®

General Specifications

Color Gray

Conduit TypeNon-toneableDensity Test MethodASTM D792A

 Density, maximum
 0.955 g/cm³ | 0.035 lb/in³

 Density, minimum
 0.941 g/cm³ | 0.034 lb/in³

Design Standard ASTM D3350-05

Wall Type Smooth

Dimensions

Length 304.8 m | 1000 ft

 Inner Diameter, nominal
 17.678 mm | 0.696 in

 Outer Diameter, nominal
 21.336 mm | 0.84 in

Wall Thickness Designation SDR 13.5

Wall Thickness, minimum 1.575 mm | 0.062 in

Nominal Size 1/2 in

Material Specifications

Flexural Modulus, minimum 551.581 N/mm² | 80000 psi

Flexural Property Test Method ASTM D790

Hydrostatic Design BasisNot pressure rated



3099979 | 050G135PP200R0PE

Hydrostatic Design Test Method ASTM D2837

Material Type High density polyethylene (HDPE) | Polypropylene

Melt Flow Rate Test MethodASTM D1238Melt Flow Rate, maximum0.39 g/10 min

Mechanical Specifications

Minimum Bend Radius, unsupported254 mm | 10 inTensile Property Test MethodASTM D638

Tensile Strength at yield, minimum 20.684 N/mm² | 3000 psi

Breaking Strength 90.718 kg | 200 lb

Pull Line Type Rope

Pulling Tension, maximum 145.15 kg | 320 lb

Environmental Specifications

Environmental Stress Crack Resistance Failure rate of 10% within 96 hours

Environmental Stress Test Method ASTM D1693, ESCR Condition B

Packaging and Weights

Weight, net 105.66 kg/km | 71 lb/kft

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



* Footnotes

Environmental Stress Crack Resistance ESCR—Environmental Stress Crack Resistence

