


E20625JCASS-24CT MICFIBR

E20® Coaxial/Fiber Hybrid Buried Cable



- E20 is a solution that enables service providers the ability to bridge HFC networks to FTTx. The E20 composite coaxial/fiber product line combines fiber, microducts, and coaxial cable under one jacket
- Serves businesses in a new commercial serving area
- Mitigates future cost of fiber installation
- Saves on initial installation due to "single sheath" vs. multiple sheaths
- Ideal for commercial data customers that also require video
- All products tested to industry standards

OBSOLETE

Product Classification

Product Type	Hybrid cable, coax and fiber
Product Brand	E20®

General Specifications

Cable Series	P3 625
Total Fiber Count	24

Dimensions

Height	26.797 mm 1.055 in
Width	19.177 mm 0.755 in
Outer Jacket Thickness, nominal	0.762 mm 0.03 in

Material Specifications

Outer Jacket Material	Medium density polyethylene (MDPE)
------------------------------	------------------------------------

Mechanical Specifications

Minimum Bend Radius	114.3 mm 4.5 in
Pulling Tension, maximum	33.112 kg 73 lb

Environmental Specifications

Environmental Space	Buried
----------------------------	--------

E20625JCASS-24CT MICFIBR

Packaging and Weights

Weight, gross 373.529 kg/km | 251 lb/kft

Regulatory Compliance/Certifications

Agency

ISO 9001:2015



Classification

Designed, manufactured and/or distributed under this quality management system

Included Products

810008925/DB
B-024-LN-8W-F12NS/16G – LightScope ZWP® Blown Micro Single Jacket All-Dielectric Outdoor Stranded Loose Tube Arid-Core® Construction Cable