# E20715JCA-24CT MICFIBR

### E20® Coaxial/Fiber Hybrid Aerial Cable



- E20 is a solution that enables service providers the ability to bridge HFC networks to FTTx. The E20 composite coaxial/fiber product line combines fiber, microducts, and coaxial cable under one jacket
- Serves businesses in a new commercial serving area
- Mitigates future cost of fiber installation
- Saves on initial installation due to "single sheath" vs. multiple sheaths
- Ideal for commercial data customers that also require video
- All products tested to industry standards

#### **OBSOLETE**

### Product Classification

Product Type Hybrid cable, coax and fiber

Product Brand E20®

General Specifications

Cable Series QR 715

**Total Fiber Count** 24

**Dimensions** 

 Height
 29.083 mm | 1.145 in

 Width
 21.463 mm | 0.845 in

 Outer Jacket Thickness, nominal
 0.762 mm | 0.03 in

Material Specifications

Outer Jacket Material Medium density polyethylene (MDPE)

Mechanical Specifications

Minimum Bend Radius127 mm | 5 inPulling Tension, maximum33.112 kg | 73 lb

# **Environmental Specifications**

Environmental Space Aerial

Page 1 of 2



# E20715JCA-24CT MICFIBR

## Packaging and Weights

**Weight, gross** 400.316 kg/km | 269 lb/kft

## Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



### Included Products

B-024-LN-8W-F12NS/16G

810008925/DB

550015392 – 75 Ohm QR® Trunk and Distribution Cable, black PE jacket QR® 715 JCA

 LightScope ZWP® Blown Micro Single Jacket All-Dielectric Outdoor Stranded Loose Tube Arid-Core® Construction Cable

©2022 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: February 25, 2022

