

# LNx-6513DS-A1M



2-port sector antenna, 2x 698–896 MHz, 65° HPBW, factory attached actuator

- Extended tilt range offers better coverage
- Great solution to maximize network coverage and capacity
- Excellent gain, VSWR, front-to-back ratio, and PIM specifications for robust network performance
- Fully compatible with Andrew remote electrical tilt system for greater OpEx savings
- The RF connectors are designed for IP67 rating and the radome for IP56 rating

## OBSOLETE

This product was discontinued on: November 30, 2023

## General Specifications

<b>Antenna Type</b>	Sector
<b>Band</b>	Single band
<b>Color</b>	Light Gray (RAL 7035)
<b>Grounding Type</b>	RF connector inner conductor and body grounded to reflector and mounting bracket
<b>Performance Note</b>	Outdoor usage   Wind loading figures are validated by wind tunnel measurements described in white paper WP-112534-EN
<b>Radome Material</b>	Fiberglass, UV resistant
<b>Radiator Material</b>	Aluminum
<b>RF Connector Interface</b>	7-16 DIN Female
<b>RF Connector Location</b>	Bottom
<b>RF Connector Quantity, low band</b>	2
<b>RF Connector Quantity, total</b>	2

## Dimensions

<b>Width</b>	301 mm   11.85 in
<b>Depth</b>	181 mm   7.126 in
<b>Length</b>	1390 mm   54.724 in
<b>Length, with installed actuator</b>	1553 mm   61.142 in
<b>Net Weight, without mounting kit</b>	14.8 kg   32.628 lb

## Electrical Specifications

# LNx-6513DS-A1M

<b>Impedance</b>	50 ohm
<b>Operating Frequency Band</b>	698 – 896 MHz
<b>Polarization</b>	±45°

## Electrical Specifications

<b>Frequency Band, MHz</b>	<b>698–806</b>	<b>806–896</b>
<b>Gain, dBi</b>	14.6	15.1
<b>Beamwidth, Horizontal, degrees</b>	65	65
<b>Beamwidth, Vertical, degrees</b>	16	14.5
<b>Beam Tilt, degrees</b>	0–10	0–10
<b>USLS, typical, dB</b>	20	20
<b>Front-to-Back Ratio at 180°, dB</b>	30	30
<b>CPR at Boresight, dB</b>	12	12
<b>CPR at Sector, dB</b>	10	10
<b>Isolation, Cross Polarization, dB</b>	30	30
<b>VSWR   Return loss, dB</b>	1.4   15.6	1.4   15.6
<b>PIM, 3rd Order, 2 x 20 W, dBc</b>	-150	-150
<b>Input Power per Port, maximum, watts</b>	400	400

## Electrical Specifications, BASTA

<b>Frequency Band, MHz</b>	<b>698–806</b>	<b>806–896</b>
<b>Beamwidth, Horizontal Tolerance, degrees</b>	±3	±3

## Mechanical Specifications

<b>Wind Loading @ Velocity, frontal</b>	202.0 N @ 150 km/h (45.4 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, lateral</b>	166.0 N @ 150 km/h (37.3 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, maximum</b>	390.0 N @ 150 km/h (87.7 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, rear</b>	205.0 N @ 150 km/h (46.1 lbf @ 150 km/h)
<b>Wind Speed, maximum</b>	241 km/h (150 mph)

## Packaging and Weights

<b>Width, packed</b>	411 mm   16.181 in
<b>Depth, packed</b>	284 mm   11.181 in
<b>Length, packed</b>	1706 mm   67.165 in

# LNx-6513DS-A1M

---

**Weight, gross** 30.9 kg | 68.123 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UK-ROHS	Compliant



## Included Products

- BSAMNT-3 – Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

## \* Footnotes

**Performance Note** Severe environmental conditions may degrade optimum performance

# BSAMNT-3



Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

## Product Classification

**Product Type** Downtilt mounting kit

## General Specifications

**Application** Outdoor

**Color** Silver

## Dimensions

**Compatible Diameter, maximum** 115 mm | 4.528 in

**Compatible Diameter, minimum** 60 mm | 2.362 in

**Weight, net** 6.2 kg | 13.669 lb

## Material Specifications

**Material Type** Galvanized steel

## Packaging and Weights

**Included** Brackets | Hardware

**Packaging quantity** 1

**Weight, gross** 6.4 kg | 14.11 lb

## Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

# BSAMNT-3

---

