

HomeConnect® Four-way Splitter, 5–1218 MHz, Dual Mount

OBSOLETE

Product Classification

 Product Type
 Coaxial splitter

 Product Brand
 HomeConnect®

General Specifications

Device Type Splitter

ApplicationIndoorOutdoorMountingHorizontalVertical

Video Ports, quantity 4

Electrical Specifications

 Insertion Loss at Frequency Band, typical
 7.2 dB @ 5-400 MHz | 8.6 dB @ 400-1218 MHz

 Return Loss at Frequency Band, input, minimum
 18 dB @ 1002-1218 MHz | 20 dB @ 5-1002 MHz

 Return Loss at Frequency Band, output, minimum
 18 dB @ 1002-1218 MHz | 20 dB @ 5-1002 MHz

Frequency Response ±0.5 dB @ 5-1218 MHz

Impedance 75 ohm

Operating Frequency Band 5 – 1218 MHz

Power Passing No

Shielding Effectiveness, minimum120 dBSpurious Signals/2nd Order Harmonics, before surge<-100 dBc</th>

Surge Capability Test Method ANSI/SCTE 81 | Category A3 (6 kV, 200 A, Ring wave)

Surge Capability Waveform 100 kHz ring wave waveform

COMMSC PE®

CSV4GD-1.2

Electrical Specifications, Isolation

@ 870-1002 MHz | 26 dB @ 65-870 MHz | 30 dB @

10-65 MHz

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +140 \,^{\circ}\text{F})$

Grounding and Bonding StandardUL 467 Ground Clamp Communication

Safety Standard SCTE

Packaging and Weights

 Height, packed
 215 mm | 8.465 in

 Width, packed
 370 mm | 14.567 in

 Length, packed
 495 mm | 19.488 in

Carton Quantity 200

Weight, gross 22.68 kg | 50.001 lb

Regulatory Compliance/Certifications

Agency Classification

CE Compliant with the relevant CE product directives

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



