NGFB-TB4QLUKOGTXXX



Next Generation Frame (NGF) Fiber Termination Block with IFC Cable, singlemode, 192 LC/UPC to Stub tail, left oriented, upward cable exit, black

1-100 meters. For additional length options, contact your CommScope representative.

Product Classification

Regional Availability EMEA | Latin America | North America

Product Type Fiber patch block, with IFC cable

Product Series NGFB

General Specifications

Functionality Patching

Application Used in NGF-style frames only

Body Style Left orientation

Cable Exit Location Upward

Cable Type IFC - Stranded

Color Black
Color, front Black

Door Type, frontCompression latch | Hinged

Growth Configuration Fully loaded

Interface, front LC/UPC
Interface, rear Stub tail

Rack TypeNGFShelf MovementFixedTotal Ports, quantity192

Material Specifications

Finish Powder coated

Material Type Steel

COMMSCOPE®

NGFB-TB4QLUKOGTXXX

Optical Specifications

Fiber Mode Singlemode

Environmental Specifications

Operating Temperature -5 °C to +50 °C (+23 °F to +122 °F)

Storage Temperature -40 °C to +70 °C (-40 °F to +158 °F)

Relative Humidity Up to 80%, non-condensing

Qualification Standards Telcordia GR-449-CORE

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant/Exempted

