



TCS2® Heat-Shrink Cable Seal, 48 inch long, 0.90 inch recovered ID, 0.08 inch recovered wall thickness

- Used for insulating and sealing underground and aerial connections in CATV plant
- Also used in low voltage (600V) electrical power distribution applications
- Thermo-chromic stripes signifying adhesive flow and sleeve recovery
- Ensures an environmental seal and protection against moisture and water penetration

OBSOLETE

Product Classification

Regional Availability	North America
Product Type	Heat shrink tubing, medium wall
Product Brand	TCS2®
Product Series	TCS2

General Specifications

Color	Black
Sealant Type	Precoated water-insoluble

Dimensions

Length	1,219.2 mm 48 in
Expanded Inside Diameter, minimum	68.6 mm 2.701 in
Recovered Inside Diameter, maximum	22.9 mm 0.902 in
Recovered Wall Thickness, nominal	2.03 mm 0.08 in

Material Specifications

Material Type	Polyolefin
----------------------	------------

Environmental Specifications

Environmental Space	Aerial
Qualification Standards	Telcordia GR-449-CORE, Issue 2

Packaging and Weights

Packaging quantity	1
Packaging Type	Bag Carton

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

