

OBSOLETE

Product Classification Coax attenuator **Product Type Product Brand** HomeConnect® General Specifications **Device Type** Attenuator Application Reduces RF signal levels by a specific value Dimensions **Contact Pin Diameter** 0.813 mm | 0.032 in **Contact Pin Diameter Tolerance** ±0.002 in **Electrical Specifications** Insertion Loss 8 dB 25 dB Return Loss, input, minimum 25 dB Return Loss, output, minimum **Frequency Response** ±0.25 dB **Operating Frequency Band** 0 - 1800 MHz Material Specifications Material Type Brass Plating Nickel

HomeConnect® Inline Attenuator, F-m/F-f, 8 dB

Page 1 of 2

©2023 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: April 3, 2023



SVFAM8

Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Safety Standard	CE EN 60728-4 SCTE	

Packaging and Weights

Height, packed	241.3 mm 9.5 in
Width, packed	241.3 mm 9.5 in
Length, packed	342.9 mm 13.5 in
Carton Quantity	2000
Weight, gross	2.54 kg 5.6 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Page 2 of 2

©2023 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: April 3, 2023

