SP-10800NNNNXABB PLC 1X8 250UM NO CONN



Wideband PLC Splitter, singlemode, 1x8, symmetrical split ratio, 0.250 mm cable, no connectors

Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117-58, §§ 70901-70953), or are the subject of a waiver approved by the Secretary of Commerce or designee.

Product Classification

Regional Availability Asia | Australia/New Zealand | China | EMEA | India | Latin

America | North America

Product Type Bare splitter

General Specifications

Device Type Component, rectangular

Functionality Splitting

Planar lightwave circuit (PLC) **Technology Type**

Distribution Type 1 x 8 splitter

Interface, Input Stub tail Interface, Output Stub tail

Split Ratio Symmetrical

Splitter, quantity

Dimensions

Pigtail Length, Output

Height 4 mm | 0.157 in Width 4 mm | 0.157 in Length 40 mm | 1.575 in Pigtail Length, Input 2.5 m | 8.202 ft 2.5 m | 8.202 ft

Pigtail Diameter, Input 0.25 mm | 0.01 in

Pigtail Diameter, Output 0.25 mm | 0.01 in

Optical Specifications

Fiber Type G.657.A2 Directivity, minimum 55 dB

COMMSCOPE®

SP-10800NNNNXABB | PLC 1X8 250UM NO CONN

Polarization Dependent Loss, maximum 0.2 dB
Uniformity, maximum 0.6 dB

Wavelength Range 1260–1650 nm

Insertion Loss, Splitter, maximum10.4 dBReturn Loss, Splitter, minimum55 dB

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C to} + 70 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to} + 158 \,^{\circ}\text{F})$

Relative Humidity 5%–95%, non-condensing

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant

