MC-DPM3M-6-96



GroundSmart® Monopole Co-location Dual Pipe Mount Kit, 12 in to 50 in OD, 4 ft 9 in face, includes pipes

Product Classification	
Product Type	Co-location dual pipe mount kit
General Specifications	
Mounting	Monopole, 304.8–1270 mm (12–50 in) OD
Pipe, quantity	6
Sectors, quantity	3
Dimensions	
Height	2,438.4 mm 96 in
Face Width	1.463 m 4.8 ft
Width	1,447.8 mm 57 in
Length	355.6 mm 14 in
Pipe Length	2,438.4 mm 96 in
Mounting Diameter, maximum	1270 mm 50 in
Mounting Diameter, minimum	304.8 mm 12 in
Pipe Outer Diameter	73.66 mm 2.9 in
Stand-off Distance	355.6 mm 14 in
Mounting Circumference, maximum	3,990.34 mm 157.1 in
Mounting Circumference, minimum	1,196.34 mm 47.1 in
Material Specifications	
Material Type	Hot dip galvanized steel

Mechanical Specifications

Wind Rating	120 mph (BWS) at 150 ft AGL 140 mph (3-second gust) at 150 ft AGL using Exposure D per FBC
Wind Rating Criteria	Two 72 in x 8 in panel antennas per sector

Page 1 of 2

©2023 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: March 23, 2023



MC-DPM3M-6-96

Wind Rating Test Method

TIA/EIA-222-G

Packaging and Weights

Included	Dual pipe frames Pipe mounts Ring mount
Packaging quantity	1
Weight, net	378.795 kg 835.1 lb

Regulatory Compliance/Certifications

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system



Agency

* Footnotes

Wind Rating BWS-Base Wind Speed; FBC-Florida Building Code

Page 2 of 2

©2023 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: March 23, 2023

